

< 1 >

O Entrust Datacard

Sigma DS2 Direct-to-Card Printer

HIGHLIGHTS

Sigma: The next generation of direct-to-card printing

Entrust Sigma ID Card Printers are specifically designed for today's cloud environments and give you the ability to easily issue secure identities.

- **Simple:** From unboxing to issuing ID cards and mobile flashpasses to managing your printer, we made sure Sigma was the most user-friendly ID card issuance solution in the world
- Secure: Our industry-leading issuance security architecture will help protect your cards and your customers' data during each step of the issuance process
- **Smart:** Forward-thinking technology and scalability allow you to expand your ID card program as your needs evolve

KEY FEATURES & BENEFITS

The world's most user-friendly ID card printer

- Intuitive printer dashboard lets you see printer status, order supplies, check cleaning status, update firmware, or contact help – all from your mobile device
- Seamless self-service lets you access how-to videos and other helpful resources by simply scanning QR code on the LCD display
- Variable LED light ring lets you incorporate brand colors or other customization into your ambient environment
- Pre-loaded ribbon cassettes make switching ribbons easy

Unmatched security

- Secure boot protects system from malware or virus on boot-up
- Trusted Platform Module (TPM) manages the printer's own TLS/SSL certificates and keys
- Connection and data sent between software and printer is encrypted
- Customer data is encrypted and is not stored in the printer after printing is complete
- Luster printing and other security features added to cards protect from tampering and counterfeiting

Flexibility and scalability built for the future

- Issuance capabilities include physical cards and digital mobile flashpass
- Choose on-premises or cloud-hosted deployment
- Expand your ID program as your needs change by adding smart card capabilities, WiFi connectivity, and more
- Print anytime, anywhere with your mobile device (iOS, Android, Windows)



TECHNICAL SPECIFICATIONS

Standard Features & Supplie	S	
Print technology	Dye sublimation	
Print capabilities	Single or dual-sided	
Print resolution	300 dots per inch (dpi) (300 X 600, 300 X 1200)	
Print speed	Single-sided color ribbon: up to 225 cards per hour (cph) Double-sided color ribbon: Up to 140 cards per hour (cph) Monochrome printing: Up to 880 single-sided cards per hour (cph)	
Card capacity	Input hopper: 125 cards Output hopper: 25 cards	
Card sizes	Thickness: 0.010 inches to 0.040 inches (0.25mm - 1.016mm) Dimension: ID-1, CR-79, CR-80	
Operating environment	Temperature: 60°F to 95°F (15°C to 35°C) Humidity: 20-80% RH – non condensing	
Physical dimensions	L 17.4 in x W 8.9 in x H 9 in / 44.2 cm x 22.6 cm x 22.9 cm	
Weight	11.3 lbs (5.49 kg); will vary with options	
Connectivity	USB and Ethernet	
Warranty	36 months	
Operating system support for printer driver	Windows 11 Windows 10, 32- and 64-bit Windows Server 2022 Windows Server 2019 Linux Ubuntu 20.04 LTS	
	Linux Kylin 10	



Optional Features & Supplies

Monochrome ribbons	Black, white, blue, red, green, scratch-off, silver matte, gold matte, silver metallic, and gold metallic: 1,500 images		
	GT-KT	500 images	
	ST-KT	500 images	
	YMCKL-KT	300 images	
	YMCKF-KT	300 images	
	KTT	750 images	
	KT	1,000 images	
	YMCKT-KT	350 images	
	ymcKT	650 images	
Color ribbons*	YMCKT	250/500 images	
	 Contactless smart card encoding: ISO 14443 A/B, ISO 15693, MIFARE, MIFARE DESFire EV1/EV2, HID Prox, iClass, iClass SE, iClass Seos, (Felica Duplex Only) 		
	 Contact smart card encoding: ISO 7816 T=0 (T=1), Class A 5V (3V and 1.8V) Contactless smart card encoding: ISO 14443 A (P. ISO 15693 MIEADE) 		
Smart card encoding	Single wire or loosely coupled:		
	Dual-band 2.4GHz & 5GHz		
	Authentication modes: None, WPA2 Personal		
WiFi	WiFi types: 802.11g/n		
	JIS Type II single-track option		
Magnetic stripe encoding	ISO 7811 three-track support (high- and low-coercivity)		

* Color ribbon guide: Y=Yellow, M=Magenta, C=Cyan, K=Black, T=Topcoat, F=UV fluorescent, L=Luster, y=1/2 panel Yellow, m=1/2 panel Magenta, c=1/2 panel Cyan, S=Silver matte, G=Gold matte.



Entrust, Sigma, and the hexagon logo are trademarks, registered trademarks, and/or service marks of Entrust Corporation in the U.S. and/or other countries. All other brand or product names are the property of their respective owners. Because we are continuously improving our products and services, Entrust Corporation reserves the right to change specifications without prior notice. Entrust is an equal opportunity employer. © 2024 Entrust Corporation. All rights reserved. DS25Q1-Sigma-DS2-Direct-to-Card-Printer-DS



Global Headquarters 1187 Park Place, Minneapolis, MN 55379 U.S. Toll-Free Phone: 888 690 2424 International Phone: +1 952 933 1223